

OGM-A-25P Flowmeter



2 Channels

OGM-A-25P Flowmeter

The OGM-A-25P series meter is a precision instrument designed for accurate measurement of diesel fuel, kerosene, oils, and other viscous liquids with a viscosity of up to 1000 cP.

Equipped with a double channel pulse output, this flow meter provides reliable and consistent measurement data for various fuel applications.

Designed for accurate measurement of diesel fuel, kerosene, oils, and other viscous liquids.

Suitable for fluids with a viscosity of up to 1000 cP, ensuring versatility in application.

Double-channel pulsar allows for precise control of the fueling process, ensuring accuracy and efficiency.

Flow range of 20-200 and pressure rating of 34 bar, suitable for a wide range of applications.

Accuracy of $\pm 0.5\%$ ensures reliable and consistent measurement results.

Ideal for use in fuel management systems, gas stations, and industrial applications requiring precise fluid measurement.

Datasheet

PULSE OUTPUT :
2 channels

DIAMETER :
1" (25mm)

ACCURACY :
 $\pm 0,5\%$

MAXIMUM VISCOSITY :
1000 cP

CONNECTION :
threaded

WORKING TEMPERATURE :
-40 to +60 C

WEIGHT :
2,8 kg

PRESSURE :
20-200 lt/minute

DIMENSION :
180 x 180 x 160 mm

REPEATABILITY :
0,03 %

FLOW RATE :
80-90L/min

